

# CORET

No.779



**Corporate Headquarters and  
Primary Manufacturing Center**

Centurio Design  
P.O.Box 1911  
48007 Muenster  
Germany  
Tel: +49 (0)251-396-38741  
Fax: +49 (0)251-396-38743  
E-Mail: [Info@CenturioDesign.com](mailto:Info@CenturioDesign.com)

**Branch for the Canadian and  
United States market**

Centurio Design Canada  
6-470 King St. West  
Suite 128  
Oshawa Ontario  
L1J 2K9 Canada  
Tel: (905) 925-6505  
E-Mail: [Contact@CenturioDesign.com](mailto:Contact@CenturioDesign.com)



# CORET<sup>®</sup> No.779

CoreT<sup>®</sup> Series, Model No. 779, a new compact weapon light concept, developed and manufactured by Centurio Design<sup>®</sup>. What makes the CoreT<sup>®</sup> Series, Model No. 779 so different from other compact weapon lights? You can remove the mount and use another one to fit the CoreT<sup>®</sup> Series, Model No. 779 to other manufactures firearms. For example, you can use Heckler & Koch<sup>®</sup> firearms which have no picatinny rail by the standards of the U.S. Military Mil-STD-1913 or by specification of the NATO STANAG 2324 such this Heckler & Koch<sup>®</sup> USP, USP SD, USP Expert, USP Elite oder for the Military version: P8. or the P2000 (Europa version), etc. So with the CoreT<sup>®</sup> Series, Model No. 779 you just change the mount and you still have a compact weapon light and you don't need any additional adapters to use the light on a Heckler & Koch<sup>®</sup> variant which of course would make the weapon heavier, making the weight of the weapon a risk for precision and safe shots. The "wings" on and off switch allow the CoreT<sup>®</sup> Series, Model No. 779 to be fitted for your pointer finger or you have the option to use a cable trigger and mount it with a Velcro strap on your handgun grip. The cable trigger is also your option to mount the CoreT<sup>®</sup> Series, Model No. 779 on Submachine Guns (SMG) / Personal Defense Weapons (PDW) or Assault, Sports and Hunting Rifles or on Shotguns.

- Light source: 3 watts LED
- Max. output: 425 Lumens
- Working mode: switching Continuous and LLLW<sup>®</sup> Strobe
- Battery type: 3.0 volts, CR123 Lithium battery, 2pcs.
- Run time: 5h
- Working temperature -40? -+85?
- Dimension: 86(L)\*41(W)\*38(H)/mm
- Net weight: 97.8g
- Hard anodized in black, coyote, and stainless steel
- Aluminum: 7075 T6
- Mount system (removable from the light body) 4 screws
- Screws: DIN EN ISO 4762, M2 and M4
- Metric thread M2 and M4, Tolerance 6H
- Surface roughness: Ra 1,6
- Made for use a Mount system Quick-detach rail



NOTE: The Mount system Quick-detach rail clamp for the CoreT<sup>®</sup> Series, Model: No779, needs to be ordered extra. Standard mount is for the picatinny rail. Heckler & Koch<sup>®</sup> or other mounts are on request.